
Series 2100


Page 1 of 2


SHOP DRAWINGS


Surface Track Pan head screw supplied by 1 5/8"manufacturer or equivalent Surface where track is attached 1 1/8" sweepstrip molding sweepstrip molding Flexible Vinyl Sweepstrip oSteel Hinge System o Finished Opening Height: Body Panel We suggest Field Measure 4 7/8 ^OSteel Hinge System 1 1/8" Nominal Flexible Vinyl Sweepstrip Finished Floor Surface





Lead Post, Jamb Moulding & Handle












Series 2100


Page 2 of 2

SHOP DRAWINGS


Intermediate Rolling Post




Privacy Latch




<u>Keylock</u>



Single Cremone Bolt Keylock



Double Cremone Bolt Key Lock



INFORMATION

Door Weight

Width Custom made to any width

Height Vinyl lam custom made to 12' -1"

Hardwood veneer custom made to 10' -1"

Panels Natural hardwood or vinyl-lam on MDF core

Panel Connector Extruded Vinyl: White, Brown or Sand

Sweep Strip Extruded Vinyl: White or Brown
Hinge System Steel: Dark Bronze or Clear

Wheels Ball bearing nylon wheels on steel axles

Track Aluminum (straight only):
Dark bronze or Clear

Lead, Intermediate and Jamb

Aluminum: White, Brown or Sand
Coordinated with panel connector

Latch

Deadlatch with thumb turn two sides

Latch Deadlatch with thumb turn two
Header Construction Detail by Others

Height
6'-8"
10lbs. Per lineal foot
8'-1"
12lbs. Per lineal foot
10'-1"
15lbs. Per lineal foot
12'-1"
18lbs. Per lineal foot

See Woodfold Accordion Door brochure for additional details

Catch/Lock Options

Magnet with strike plate

Privacy Latch Deadlatch with thumb turn one side
Springlatch Springlatch with thumb turn two sides

Keylock 1 Side Deadlatch with thumb turn one side, keylock one side

Keylock 2 Side Deadlatch with keylock two sides
Single Cremone Single cremone bolt with keylock
Double Cremone Double cremone bolt with keylock

Footbolts Locking or non locking

Other Keyed Options Keyed alike, custom keyed, construction core Contact manufacture for more details

Job Name: _____ Ard

Architects Acceptance

Qty. Single/Pair Single End/Double End Left or Right Stack Width X Height Finish/Color Comments

Supplier:

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Woodfold Manufacturing. Inc. P.O. Box 346 Forest Grove, OR. 97116 http://www.woodfold.com

Phone: 503-357-7181 Fax: 503-357-7185 2100 SD 3/00